



Wolver Gear Oil GL-5 80W-90

VERPACKUNG

208 L | 60 L | 20 L | 1 L

WOLVER Gear Oil GL-5 SAE 80W-90 is a hypoid gear oil for mechanical gears based on high-quality, solvent refining basic oils.

WOLVER Gear Oil GL-5 SAE 80W-90 multi-purpose gear oil: To avoid seasonal change of gear oil **WOLVER Gear Oil GL-5 SAE 80W-90** multi-purpose gear oil is available with the viscosity categorie SAE 80W-90 and thus can be applied in winter as well as in summer.

The universal application of **WOLVER Gear Oil GL-5 SAE 80W-90** reduces the risk of confusion and simplifies stockkeeping. The balanced combination of additives guarantees properties like high pressure susceptibility, exceptional good viscosity-temperature behaviour. High oxidation stability, low pour point, good wear protection and avoids black sludge formation.

SPECIFICATIONS:

SAE 80W-90
API GL-5

MEETS THE REQUIREMENTS OF:

CLARK FORM ALC-1 5M Rev.7-80 KE, TLC-25 3M GAC 4-78, CS 3000 B, EATON BULLETIN 6007, 2052, 2053, FORD M-2C-9022 A / SM-2C-1011-A / EST-M2C-108C, FULLER FORM 121, JI CASE MS 1316, JOHN DEERE JDM J 11D/E, KOMATSU DRESSER B22-0003, B22-0005, MACK GO-G,

MAN 342 N / 342 Typ M2 (160.000 km.)
MB 235.0, 235.6, ROCKWELL INTERNATIONAL 0-76,
TEREX EEMS 19003,
VME AMERICAS EEMS 19003 F, VOLVO 97310, 97313
ZF TE-ML 05A,
07A,08,12E,16B/C/D,17B,19B,21A,
DAF
Renault

Characteristics

- Very well wear protection
- Good sticking and pressure-bursting lubrication film
- First-rate oxidation stability
- Exceptional good viscosity temperature behaviour
- Neutral towards metals and sealing materials
- No foaming

Effects

- Optimal operating properties
- Reduces wear and background noises
- Multi-purpose Hypoid-gear-oil
- Reducing of wearing in a wide application range
- Engine oil for all seasons

Application

- Motor vehicle axle drive (differential gear) according API GL 5
- High loaded gear boxes according API GL 5
- Distributors-, intermediary- and auxiliary gearboxes in cars and working machines

Recycling

WOLVER Gear Oil GL-5 SAE 80W-90 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Gear Oil GL-5 SAE 80W-90 gear oil of hypoid range is fully tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **WOLVER Gear Oil GL-5 SAE 80W-90** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	15.4
Viscosity index	-	89
Pour point	°C	-28
Total acid number	mgKOH/g	0.7
Flash point	°C	228
Density at 15.6 °C	kg/m ³	899

1L - Can	4131	4260360941313
4L - Can	4205	4260360942051
20L - Pail	4065	4260360940651
60L - Barrel	4197	4260360941979
208L - Barrel	4035	4260360940354