



WOLVER Hydrauliköl HVLP 68

VERPACKUNG

208 L | 60 L | 20 L

Wolver Hydraulik HVLP 68 – it is zinc-containing working fluids on a mineral basis, which have excellent viscosity-temperature properties and a corresponding all-season characteristic. Due to this, the maximum smoothness of the hydraulic system operation is guaranteed, even under extreme temperature fluctuations and when the system is started up.

SPECIFICATIONS:

HVLP 68
DIN 51524 Teil 3
ISO HV

MEETS THE REQUIREMENTS OF:

BOSCH Rexroth
SEB 181222
ANFOR NF E 48-603 (HM, HV)
SIS SS 155434
Denison Filterability TP 02100
Hoesch HWN 2333
U.S.Steel 126 u., 127
CETOP RP 91 H (HM, HV)
Sperry Vickers M-3950-S u., I-286-S
FZG-Test A 8,3/90 12

Characteristics

- Designed for modern hydraulic systems.
- Particularly recommended for hydraulic systems operating year-round in the open air.
- Recommended for systems subject to strong temperature fluctuations (barriers, baling presses, sluices, dams).
- They are used in hydrostatic systems of construction machines, forklift trucks, container trucks and municipal vehicles.

Effects

- Excellent protection against wear and aging
- High shear stability and oxidation resistance
- Improved protection against bullying
- Excellent viscosity-temperature properties

- All-season characteristic
- Improved corrosion protection
- Excellent demulsibility

Utilisation

- Uninterrupted operation even in systems made of different metals
- Long oil life
- Reducing wear and tear under severe operating conditions, especially when impact loads
- Designed mainly for equipment operating in a cold climate (mountainous terrain, winter sports zones, winter road service, refrigerators, freezers)
- Reduced assortment of used lubricants - simplification of orders and logistics
- Long service life of equipment
- Protection against penetrating water

Disposal

Wolver Hydrauliköl HVLP 68 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

Wolver Hydrauliköl HVLP 68 of HLP range is well-tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **Wolver Hydrauliköl HVLP 68** of HLP range when refilling.

Data table

| PROPERTIES | UNIT | TYPICAL INDICATORS |
|------------------------------|--------------------|--------------------|
| Kinematic viscosity at 40 °C | mm ² /s | 68.2 |
| Viscosity index | - | 134 |
| Pour point | °C | -42 |
| Total acid number | mgKOH/g | 0.9 |
| Flash point | °C | 216 |
| Density at 15.6 °C | kg/m ³ | 878 |

20L - Pail 4219 4260360942198

208L - Barrel 4224 4260360942242

208L - 4260360942242 , 20L - 4260360942198