



Wolver Modelux EP2

VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

WOLVER MODELUX EP2 - high anti-wear and extreme pressure grease. It meets the requirements of the automotive industry as a universal automotive lubricants.

WOLVER MODELUX EP2 - universal lithium grease is recommended for year-round use, as the main lubricant for automotive park and car owners in normal operating conditions.

Operating Temperature Range: -30 ° C ... + 120 ° C

SPECIFICATIONS

NLGI 2 · KP2K-30 ·
L-XCCEB 2

Characteristics

- wear protection at high loads and speeds;
- provides long-term protection against corrosion even under water, snow, dirt and dust influence;
- it provides mechanical and thermal stability;
- reliable sealing mechanism nodes.

Utilization

- Hub bearings, ball bearings, cardan shaft crosses, steering gear and other chassis components of cars and trucks;
- Accessory mechanisms for automobiles, such as windows, water pump bearings, generator bearings, cables, hinges and locks, slides, winches, etc .;
- Rolling and plain bearings, bushings, shafts, pins and other components of industrial friction, agricultural, lifting and transport, garage and power equipment under normal operating conditions.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
------------	------	--------------------

Viscosity of Oil at 40°C	mm ² /s	152
Penetration at 25°C	10 ⁻¹ .mm	275
Dropping point	°C	198
Anti-corrosion properties	-	pass
Weld Load 4-Ball	kg	250
Colour	-	yellow

10L - Pail	4220	4260360942204
20L - Pail	4069	4260360940699
208L - Barrel	4039	4260360940392
400g - cartridge	4051	4260360940514