



## Wolver Super Dynamic Diesel 10W-40

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 1 L

**Wolver Super Dynamic Diesel SAE 10W-40** is a semi-synthetic motor oil for all types of diesel engines with a new, improved formulation. It is based on base oils and additives that ensure engine cleanliness, economy, safety and durability.

**Wolver Super Dynamic Diesel SAE 10W-40** has excellent viscosity-temperature characteristics, which guarantees engine protection when operating in a wide temperature range and various operating conditions

**Wolver Super Dynamic Diesel SAE 10W-40** is especially effective in the diesel engines of cars and commercial vehicles of both the early years of production and modern, according to recommendations of automakers.

SPECIFICATIONS:  
SAE 10W-40  
API CF  
ACEA A3/B3, A3/B4

MEETS THE REQUIREMENTS OF:  
MB 229.1  
VW 501.01/505.00  
BMW Special

### ***Characteristics***

- Extreme wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

### ***Effects***

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption

- Optimal engine cleanliness
- Low oil consumption
- All-year-round operation

### ***Application***

- high-performance and normal four-stroke diesel engines
- with multivalve technology
- with catalyst technology
- with turbocharging
- without turbocharging
- CDI- HDI- and TDI-motors
- with CDi-technology
- with catalyst technology

### ***Recycling***

- **WOLVER Super Dynamic Diesel SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

### ***Miscibility***

- **WOLVER Super Dynamic Diesel SAE 10W-40** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Dynamic Diesel SAE 10W-40** when refilling.

### ***Data table***

| PROPERTIES                    | UNIT               | TYPICAL INDICATORS |
|-------------------------------|--------------------|--------------------|
| Kinematic viscosity at 100 °C | mm <sup>2</sup> /s | 14.7               |
| Viscosity index               | -                  | 150                |
| Pour point                    | °C                 | -30                |
| Viscosity CCS at -25°C        | mPa·s              | 6100               |
| TBN                           | mgKOH/g            | 9.1                |
| Flash point                   | °C                 | 220                |
| Density at 15.6 °C            | kg/m <sup>3</sup>  | 866                |

|          |      |               |
|----------|------|---------------|
| 1L - Can | 4410 | 4260360944109 |
| 5L - Can | 4412 | 4260360944123 |