



Wolver Super Fluid ATF 3000

VERPACKUNG

208 L | 60 L | 1 L

WOLVER Super Fluid ATF 3000 ATF DEXRON III H automatic transmission fluid is a development of ATF transmission oils. Carefully selected mineral and HC-Synthetic base oils and modified additive and effective ingredient combinations make the quality of this ATF perfect. It is a special transmission oil for use in modern, self-engaging vehicle transmissions.

WOLVER Super Fluid ATF 3000 overlaps the requirements of DEXRON II D, DEXRON III F, DEXRON III G ATFs.

Outstanding ageing and oxidation stability makes it **WOLVER Super Fluid ATF 3000** suitable for lifetime applications (Note manufacturer's manual).

SPECIFICATIONS:

ATF-DEXRON III H / III G / III F

MEETS THE REQUIREMENTS OF:

ALLISON C-4/TES 389
CATERPILLAR TO-2
CHRYSLER MS-9602, MS-7176
FORD MERCON
FORD M2C 138-CJ, 166-H
MAN 339 Typ Z1 & V1, Z2 & V2
MB 236.1, 236.5, 236.6, 236.7

VOITH 55.6335, 55.6336

VOLVO 97340, 97341

ZF TE-ML 02F, 04D, 09, 11A, 14A, 17C

Characteristics

- Extreme wear protection
- High thermo stability
- Optimum foaming behaviour
- Optimum matched friction behaviour
- High load capacity
- High oxidation stability
- Excellent viscosity-temperature behaviour
- Extreme low pour point
- Neutral towards metals and sealing materials

Effects

- Optimal operating reliability at extreme conditions
- Excellent cold flow qualities
- Best lubrication
- All-year operation
- Reduces kinds by universal property

Application

- Passenger car automatic gear
- Passenger car gear box according service instructions
- Passenger car servo steering according service instructions
- Vehicle hydraulic plants according service instructions
- Fluid couplings on vehicles in accordance with manufacturer's specifications
- Hydrodynamic converters on vehicles in accordance with manufacturer's specifications

Not suitable for use in DCT/DSG- or CVT-transmissions

Recycling

WOLVER Super Fluid ATF 3000 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Super Fluid ATF 3000 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Fluid ATF 3000** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	7.8
Viscosity index	-	179
Pour point	°C	-46
Flash point	°C	205
Density at 15.6 °C	kg/m ³	859

1L - Can	4129	4260360941290
20L - Pail	4307	4260360943072
208L - Barrel	4048	4260360940484