



Wolver Super Light 10W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Super Light SAE 10W-40 is an highly alloyed lightrun petrol and diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines.

WOLVER Super Light SAE 10W-40 used for all-year-round application in modern gas and diesel engines (no carbon formation, which is confirmed by excellent test results). It provides high engine cleanliness, including engines with turbocharging and catalyst.

SPECIFICATIONS:

SAE 10W-40
API SN/CF
ACEA A3/B3, A3/B4
ILSAC GF-4

MEETS THE REQUIREMENTS OF:

MB 229.3
VW 501.01/505.00
502.00/505.00
BMW LL-01

Characteristics

- Extreme wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness

- Low oil consumption
- All-year-round operation

Application

- high-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- passenger car diesel engines
- with turbocharging
- without turbocharging
- CDI- HDI- and TDI-motors
- with CDi-technology
- direct-injection
- with catalyst technology

Recycling

- **WOLVER Super Light SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Super Light SAE 10W-40 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Light SAE 10W-40** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	14.1
Viscosity index	-	159
Pour point	°C	-33
Viscosity CCS at -25°C	mPa·s	6400
TBN	mgKOH/g	8.2
Flash point	°C	212
Density at 15.6 °C	kg/m ³	873

1L - Can	4105	4260360941054
4L - Can	4003	4260360940033
20L - Pail	4061	4260360940613
60L - Barrel	4191	4260360941917
208L - Barrel	4031	4260360940316