



Wolver Super Traffic 10W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER Super Traffic SAE 10W-40 - multigrade semisynthetic universal motor oil. Used for gas and diesel engines as well as engines operating on natural gas (LPG - a mixture of propane and butane or CNG - methane) turbocharged and naturally aspirated engines of passenger cars, vans and light trucks. Recommended for year-round use in various operating conditions: urban, extra-urban, start-stop mode. Ideal for mixed fleets.

WOLVER Super Traffic SAE 10W-40 meets the requirements and oil specifications for major European, American and Asian engine manufacturers.

WOLVER Super Traffic SAE 10W-40 helps to reduce engine operating clearances, leads to a reduction in oil consumption and, consequently, to a decrease the oil refilling.

SPECIFICATIONS:
SAE 10W-40
API SJ/CF-4
ACEA A3/B3, E2

MEETS THE REQUIREMENTS OF:
MB 228.1, 229.1
VW 501.01/505.00
VOLVO VDS
MAN 271

Characteristics

- Stable viscosity and low burning oil consumption
- High resistance to aging and oxidation
- Reduces formation of aging products at high temperatures
- Excellent cold starting properties - fast supply to all lubrication points
- Excellent low temperature pumpability
- Reduced scuffing and bore polishing
- Reduces fuel consumption

Effects

- German reliability
- Increase the service life of seals and gaskets, extended drain intervals

- Minimum wear at high loads to the driving parts
- Reduces the starting load on the engine
- All-year operation
- Increase operational efficiency and reduce overall costs
- Keeps stable oil film at all operating conditions
- Ensures the viscosity stability, in case the engine condition is satisfactory, when the penetration of fuel or coolant into the oil excluded

Application

- universal motor oil for mixed fleets
- gas and diesel engines of passenger cars, light trucks and vans, as well as engines running on LPG
- engines with dual fuel system (liquefied petroleum gas - gas, liquefied petroleum gas - diesel)
- turbocharged
- with the catalyst
- early year of manufacture engines, including long service life engines.

Recycling

- **WOLVER Super Traffic SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER Super Traffic SAE 10W-40 is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER Super Traffic SAE 10W-40** it is recommendable to use only **WOLVER Super Traffic SAE 10W-40** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	877
Viscosity at -25°C	cP	4325
Viscosity at 100°C	cSt	14,7
Viscosity index		158
Flash point COC	°C	230
Pour point	°C	-32
TBN	mgKOH/g	8,6

5L 4260360942501

4L 4260360942525

1L 4260360942549

20L 4260360942563

Barel 4260360942570

60L 4260360942679