



## Wolver SuperTec 5W-30

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER SuperTec SAE 5W-30** is a hightec synthetic lightrun motor oil especially developed for heavy duty gas and diesel car engines.

**WOLVER SuperTec SAE 5W-30** meets the manufacturers` high quality demands for cars. It is excellently applicable for long drain intervals and for motors with direct injection. Ideal for hard use at motorways and over short distances.

### SPECIFICATIONS:

SAE 5W-30  
API SN/CF  
ACEA A3/B3, A3/B4

### MEETS THE REQUIREMENTS OF:

MB 229.3  
MB 229.5  
VW 502.00/505.00  
VW 501.01/505.00  
PSA B71 2296  
PSA B71 2300  
BMW LL - 01  
RENAULT RN0700  
RENAULT RN0710  
GM-LL-B025

### Characteristics

- Extreme wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

### Effects

- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication

- Very good operating reliability
- Optimal engine cleanliness
- Low oil consumption
- High performance characteristics and high product stability
- Extended drain intervals
- Prevents black sludge formation
- All-year round operation

### **Application**

- high-performance and normal four-stroke gas engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- passenger car diesel engines
- with turbo charging
- direct-injection
- with CDi-technology

### **Recycling**

- **WOLVER SuperTec SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER SuperTec SAE 5W-30** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER SuperTec SAE 5W-30** it is recommendable to use only **WOLVER SuperTec SAE 5W-30** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	11.6
Viscosity index	-	163
Pour point	°C	-36
Viscosity CCS at -30°C	mPa·s	6200
TBN	mgKOH/g	9.3
Flash point	°C	220
Density at 15.6 °C	kg/m <sup>3</sup>	843

1L - Can	4137	4260360941375
4L - Can	4139	4260360941399
20L - Pail	4067	4260360940675
60L - Barrel	4266	4260360942662
208L - Barrel	4037	4260360940378

1л - банка	4137	4260360941375
4л - банка	4139	4260360941399
20л - ведро	4067	4260360940675
60л - бочка	4266	4260360942662
208л - бочка	4037	4260360940378