



Wolver SuperTec 5W-40

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER SuperTec SAE 5W-40 - synthetic motor oil for efficient and economical engine operation. It provides easy "cold start" in winter conditions. Developed specifically for heavy duty gas and diesel engines of passenger cars.

WOLVER SuperTec SAE 5W-40 meets the manufacturers high quality demands. For low viscosity performance fully synthetic base oils used.

SPECIFICATIONS:
SAE 5W-40
API SN/CF
ACEA A3/B3, A3/B4

APPROVALS:
MB-Approval 229.3

MEETS THE REQUIREMENTS OF:
MB 229.5
VW 502.00/505.00
VW 501.01/505.00
PSA B71 2296
PSA B71 2300
BMW Longlife-01
RENAULT RN0700
RENAULT RN0710
OPEL GM-LL-B025

Characteristics

- Extreme wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxydation- and thermo stability

Effects

- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability

- Optimal engine cleanliness
- Low oil consumption
- High performance characteristics and high product stability
- Extended drain intervals
- Prevents black sludge formation
- All-year round operation

Application

- High-performance and normal four-stroke gas engines
 - with multivalve technology
 - with turbo charging
 - with catalyst technology
- Passenger car diesel engines
 - Suction diesel
 - Turbo diesel
 - with CDi-technology
 - Direct-injection
 - with catalyst technology

Recycling

- **WOLVER SuperTec SAE 5W-40** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER SuperTec SAE 5W-40 is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER SuperTec SAE 5W-40** it is recommendable to use only **WOLVER SuperTec SAE 5W-40** when refilling.

Data table

| PROPERTIES | UNIT | TYPICAL INDICATORS |
|-------------------------------|--------------------|--------------------|
| Kinematic viscosity at 100 °C | mm ² /s | 14.3 |
| Viscosity index | - | 171 |
| Pour point | °C | -35 |
| Viscosity CCS at -30°C | mPa·s | 4800 |
| TBN | mgKOH/g | 9.2 |
| Flash point | °C | 216 |
| Density at 15.6 °C | kg/m ³ | 847 |

| | | |
|---------------|------|---------------|
| 1L - Can | 4107 | 4260360941078 |
| 4L - Can | 4001 | 4260360940019 |
| 20L - Pail | 4060 | 4260360940606 |
| 60L - Barrel | 4190 | 4260360941900 |
| 208L - Barrel | 4030 | 4260360940309 |