



Wolver Turbo Evolution 15W-40

VERPACKUNG

208 L | 20 L | 5 L | 1

WOLVER Turbo Evolution 15W-40 is a highly effective engine oil of a new level of modern vehicles and stationary engines, which is a product of the evolution of API CI-4 oil (2002 publication) to higher requirements of ACEA E7 (2016 revision).

WOLVER Turbo Evolution 15W-40 is produced with the use of an advanced and balanced additive package - Stable Protect, which allows to ensure optimum productivity, thermal, viscosity and antioxidant stability during a long period of exploitation.

WOLVER Turbo Evolution 15W-40 is especially effective in engines of commercial vehicles, medium-loaded engines of main trucks, agricultural and quarry equipment. Complies with the current environmental standards EURO 5/4/3 and can be used in engines with EGR and / or SCR exhaust gas cleaning technologies without a particulate filter.

SPECIFICATIONS:
SAE 15W-40
API CI-4/SL
ACEA A3/B4, E7

MEETS THE REQUIREMENTS OF
MB 228.3 MB 229.1
Volvo VDS-3
Mack EO-M Plus / EO-N RENAULT VI, RLD-2
MAN M 3275
Cummins CES
20071/-72/-75/-76/-77/-78
MTU 2
IVECO
Caterpillar ECF-1-a
ALLISON C-4
Voith Retarder Typ A

Characteristics

- Full Saps technology
- Low evaporation and high stability
- Excellent viscosity-temperature behaviour
- Reduces formation of ageing products at high temperatures
- Optimal protection against corrosion, oxidation, wear and foaming
- Extremely high pressure susceptibility

- Highest wear protection

Effects

- Meets the requirements of ecological standards EURO 3/4/5
- All-year-round operation
- Easy start in cold season;
- Provides lower fuel consumption.
- Excellent viscosity characteristics even during extended drain intervals
- Prevents black sludge formation
- Protection against reflector surface formation
- Minimum wear at highly strained engines
- Versatility, which reduces the number of varieties of consumed oil for mixed fleets

Utilization

- **commercial vehicle diesel engines**

- with turbo charging
- with catalyst technology
- with EGR technology
- with SCR technology

- **passenger car diesel engines**

- with turbo charging
- with catalyst technology

- **four-stroke petrol engine**

- with turbo charging
- with multivalve technology
- with catalyst technology

Disposal

Wolver Turbo Evolution SAE 15W-40 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

Wolver Turbo Evolution SAE 15W-40 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **Wolver Turbo Evolution SAE 15W-40** when refilling.

Data Table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	16.0
Viscosity index	-	155
Pour point	°C	-32
Viscosity CCS at -20°C	mPa·s	6800
TBN	mgKOH/g	10.2
Flash point	°C	230
Density at 15.6 °C	kg/m ³	865

20L - Pail 4395 426036094395
 60L - Barrel 4397 426036094397
 208L - Barrel 4396 426036094396

