



Wolver UltraTec 5W-30

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER UltraTec SAE 5W-30 is a newly-developed universal light-running multigrade motor oil based on special synthetic base oils of the latest technology. Carefully selected, highly-efficient additives give this high-performance motor oil outstanding properties in vehicle operation.

WOLVER UltraTec SAE 5W-30 is a universal, fuel-saving, specially-composed, super-high-tech, light-running motor oil that exceptionally fulfils the qualities of modern gas and diesel engines - with and without turbo chargers - in passenger cars and vans, with extended drain intervals, including particulate filters (ACEA C3).
In addition, this motor oil extends the life of the particulate filter.

On the basis of its special composition, **WOLVER UltraTec SAE 5W-30** is exceptionally suited for use according to the newest VW 504.00/507.00 requirements, so-called VW Longlife III oils.

This high-performance engine oil can be used in other VW engines of all types, except R5, V10 TDI pump-jet engines with and without DPF diesel particulate filter, where the specifications VW 503.00, 506.00, 506.01 are required.

SPECIFICATIONS:

SAE 5W-30
API SN/CF
ACEA C3

APPROVALS

MB-Approval 229.51
VW-Norm 504.00/507.00

MEETS THE REQUIREMENTS OF:

MB 229.31
MB 229.52
GM Dexos 2
PORSCHE C30
BMW Longlife-04
Ford WSS-M2C 917A

Characteristics

- Extreme wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxydation- and thermo stability
- Low volatilization loss

- Very high cleaning capability
- Particularly low emission combustion

Effects

- Reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission
- Reduced ash formation (Low SAPS)
- Light motor start
- Optimal engine cleanliness
- Very low resistance an motor starting
- Very good operating reliability
- High power reserve
- Extended drain intervals
- All-year round operation

Application

- VW and other new high-performance and normal four-stroke gas engines with and without WIV systems
- with multivalve technology
- with turbo charging
- with catalyst technology
- with extended drain interval
- VW and other new diesel engines with and without WIV systems
- with pump and nozzle engines
- with diesel particulate systems (DPF)
- with CDi-technology
- with turbo charging
- with multivalve-technology
- with catalyst technology

Recycling

- **WOLVER UltraTec SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER UltraTec SAE 5W-30 is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **WOLVER UltraTec SAE 5W-30**, however, the use of **WOLVER UltraTec SAE 5W-30** is worth recommending.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	11.9
Viscosity index	-	158
Pour point	°C	-36
Viscosity CCS at -30°C	mPa·s	5350
TBN	mgKOH/g	6.3
Flash point	°C	224
Density at 15.6 °C	kg/m ³	849

1L - Can	4258	4260360942587
4L - Can	4093	4260360940934
20L - Pail	4303	4260360943034
60L - Barrel	4330	4260360943300
208L - Barrel	4304	4260360943041

