



Wolver UTTO 80W

VERPACKUNG

208 L | 60 L | 20 L

WOLVER UTTO is a first-rate multigrade oil and can be used for farm tractors, forklift trucks of all manufacturers as hydraulic and gear oil. It is suitable for units with wet brakes and clutches (neck shaft coupling).

Due to modern technology the oil has high performance and ensures reliable operation of hydraulic and brake systems, powertrain agricultural machinery in heavy duty operation.

The product is not intended for use as motor oil.

SPECIFICATIONS:

SAE 80W
API GL-4
DIN HLP-D/HVLP-D (ISO VG 46-68)

MEETS THE REQUIREMENTS OF:

DENISON HF-0, HF-1, HF-2
SPERRY VICKERS I-286-S, M-2950-S
ALLISON C4,
MIL-L-2105,
CATERPILLAR TO-2,
ZF TE-ML 05F, 17E
ALLISON C3,
CASE MS-1204, MS-1205, MS-1206, MS-1207, MS-1209, MS-1210

CASE NEW HOLLAND MAT 3525, 3505
DEUTZ Hydr. Trans Fluid
DENISON HF 1/2/3
JOHN DEERE J 20C/D
MASSEY FERGUSON M-1110, M-1127 A, B;
M-1129 A; M-1135; M-1139; M-1141; M-1143; M-1145
VALMET/VOLVO BM
ZF TE-ML 03E/06

Characteristics

- Excellent viscosity-temperature behaviour
- Excellent detergent- and dispersant characteristics
- High viscosity index
- Good anti-foaming behaviour
- Excellent wear and corrosion protection
- High ageing stability

Effects

- Affords an undisturbed operation of gears, hydraulic and brake systems
- Low pour point

- All-year operation

Application

- Gears, back axles, immersion brakes of tractors and fork lift trucks.
- Moving hydraulic systems such as cranes, branch clutches, power steerings.
- Axles and hypoid traktor clutches according to API GL 4
- Forestry and construction machinery

Recycling

WOLVER UTTO is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER UTTO is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **WOLVER UTTO** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm ² /s	10.8
Viscosity index	-	132
Pour point	°C	-36
Viscosity CCS at -25°C	mPa·s	6800
TBN	mgKOH/g	8.7
Flash point	°C	230
Density at 15.6 °C	kg/m ³	878

20L - Pail	4073	4260360940736
60L - Barrel	4199	4260360941993
208L - Barrel	4044	4260360940446